

Fit Collection

Basic Fit | Premium Fit

Rolls and Interlocking Tiles

The Fit Collection is the “original” recycled rubber fitness floor. Available in rolls and tiles, this durable surface sets the standard for performance, quality, and affordability.

Product Attributes

- **8mm Vulcanized Composition Rubber (VCR)**
A durable surface that provides ergonomic benefits and is slip resistant—wet or dry

Nominal Dimensions

Available as a standard in rolls and interlocking tiles. Talk to your local sales rep to determine availability, pricing, minimums, and lead times. See the Tech Manual and Guide Specs for installation instructions and product specifications.



8mm x 48" (1.2m)
6mm x 48" (1.2m)*
9mm x 48" (1.2m)*

*Available in ELOO, ELO1, and ELO2, ELO5 only



8mm x 23" (.58m) x 23" (.58m)

Applications

- Free Weights
- Therapy / Rehab
- Cardio
- Retail
- Public Spaces
- Selectorized Strength
- Childcare / Playzones
- K-12 / Higher Education

Benefits

- Durable
- Sustainable
- Easy to maintain
- Slip-resistant
- Interlocking tiles are quick & easy to install



NRG



Force Reduction: 10.4%
Absorption of impact energy




Energy Restitution: 71.9%
Useful return of impact energy

Typical Deltec Field Tester Results

Color Swatches

BASIC FIT




Buff Blue / Gray 10 ELO4




Rippin Red / Gray 10 ELO6



Grippin Gray 10 ELO2



Buff Blue 10 ELO1




Rippin Red 10 ELO5



Yellow Surge ELO7



Pumpin Purple ELO9




Green Tea 3 EL32B

PREMIUM FIT




Steel Appeal 2 EL15A




Dark Gray EL502




Mocha Latte 2 EL43A




Raiders EL503




Blue Jays EL103




Cardinals EL104



Wildcats 3 EL100B




Gators 3 EL107B




Tigers EL106




Lions EL102




Vikings EL101




Grippin Gray 20 EL46




Buff Blue 20 EL45




Whey Protein 2 EL97A



Rippin Red 20 EL47




Jet Black ELO0




Rustic Edge EL512



Raw Titanium EL513



Forged Steel EL514



Urban Slate EL515

Technical Details

Performance Criteria	Test Standard	Typical Results
Recovery after Static Load (@1,000 PSI)	ASTM F970 Modified	0.020"
Coefficient of Friction	ASTM D2047	>0.8
FloorScore	CA 01350	Certified
Abrasion Resistance	ASTM D3389	Pass
Flammability- Pill Test	ASTM D2859	Pass
Impact Insulation Class (IIC)*	ASTM E492	51
Delta IIC*	ASTM E2179	22

*Tested on a 6" concrete slab with no ceiling.